

Analogue Linear Heat Detection Cable, Nylon Sheath



Overview

The Analogue Linear Heat Detection cable in a nylon outer sheath that provides additional UV protection making it suitable for external applications where it may be subjected to sunlight. It also provides protection against the elements and some chemicals. It is supplied in 100m and 500m lengths.

In temperature sensitive environments early detection of an abnormal change is crucial to protect safety of life, critical processes and reduce losses. The AA analogue range of linear heat detection cable use exceptionally durable linear heat detection technologies which provide extensive and continuous coverage, is easy to install and fully integrate with building management systems. The products offer an enviable set of features bringing enhanced benefits and increased safety to the fire protection industry worldwide.

Fast Response Time

This unique sensor cable and its method of control continuously responds to changes in temperature. The technology offers the facility to programme an early warning pre-alarm as well as the specified alarm temperature. If the temperature surrounding the cable reaches the pre-alarm point, the control unit triggers a warning giving the user time to survey the area at risk. Only when the temperature reaches the specified set alarm point will the control unit trigger full alarm.

The Controller

The optional two stage programmable alarm settings make the system and method of overheat detection incredibly flexible and ideal for use in a variety of different environments and applications. The technology automatically compensates for changes in the ambient temperature to maintain the accuracy of alarm temperature as well as offering up to 500 metres of continuous detection per control unit.

Both versions of control unit carry UL521 approval. One is a self-contained unit or, for finer control, a version requiring a PC prevents uninvited system access. Both designs are compatible with any conventional or addressable fire alarm panel or other building management system.

Rest and Reuse

Analogue LHD cable is 'self-restorable' which means it is not always necessary to replace the cable after an incident. Once the alarm has been triggered and depending on the severity of the incident, the system can simply be reset with minimum disruption and inconvenience.

Standard Features

- UL521 approved, RoHS compliant and CE certified to meet end user specifications
- Open and short circuit detection reduces the risk of false alarms
- Optional pre-alarm, setting allows the user to manage risk more effectively
- Cable based sensing allows detection at the point of risk
- Low installation and maintenance costs reduce total cost of ownership
- Suitable for installation in hazardous areas
- Approved to the latest standards



Australia & New Zealand

Phone: 1800 672 171
Outside Australia: +61 3 9518 5588
Email: firesecuritycs@carrier.com
Web: www.kidde.com.au

Head Office

10 Ferntree Place
Notting Hill, Victoria 3168
Australia

© 2020 Carrier. All rights reserved.
Kidde Australia is a Carrier company.

Specifications

	100m	500m
Mechanical		
Outside diameter (Nominal)	5.50mm ± .0.75mm	
No of cores	4	
Core colours	Red, White, Clear, Clear	
Zone length (min to max)	30.5mm to 500,	
Weight	3.190kg	15.950kg
Environmental		
Operating temperature limits	-40°C to +125°C	
Operating temperature (continuous)	-40°C to +90°C	
Relative humidity	0% to 99%	

Ordering information

Part number	Description
AAN-0100	Alarmline II Analogue LHD Cable with Nylon Sheath, 100m
AAN-0500	Alarmline II Analogue LHD Cable with Nylon Sheath, 500m
AACULP	Alarmline II Analogue LHD Control Unit - PC Programmable
AACUSP	Alarmline II Analogue LHD Control Unit - Self Programmable